

# FLOOR CARE *Solutions*



## ***Evolution***<sup>®</sup> ***HIGH SOLIDS FLOOR FINISH*** ***Green Certified High Gloss Finish***



- 22% solids content provides high gloss and extended durability
- Low-odor formulation can be applied while building is occupied
- Green Seal certified (GS-40)



CARE FOR WORK ENVIRONMENTS<sup>®</sup>

# Ecolution® HIGH SOLIDS FLOOR FINISH

## Green Certified High Gloss Finish

### SAFER FORMULATION

Ecolution® High Solids Floor Finish is an active formulation of styrene/ acrylic copolymers that do not contain zinc as a cross-linking agent. This special formulation provides high gloss and durability and resists scuffing, black marking and powdering to help maintain its original appearance.

### HIGH GLOSS AND DURABILITY

Ecolution® High Solids Floor Finish has a 22% solids content which results in a showroom look and durable protection for longer periods of time. Its self-leveling properties guarantee an even, beautiful finish that is easily removed with Ecolution® Floor Stripper. Plus, the finish meets required slip-resistance testing, providing a safe floor to walk on in high-traffic environments.

### DIRECTIONS FOR USE:

Please review label and SDS for all product directions, precautions and first aid information.

1. Remove all old finish using Ecolution® Floor Stripper
2. Rinse floor with cool water, making sure all residue is removed
3. Apply Ecolution® High Solids Floor Finish using a rayon mop or lambswool applicator
4. Allow 45-60 minutes of dry time between coats, more if humidity is high
  - For best results, apply five coats of finish to the floor
  - Never pour any unused finish back into its original container
5. Wait 24 hours until burnishing with a high speed machine

Dispose of unused product in accordance with Federal, state and local regulations. Use product in accordance with prescribed use dilutions. Empty containers can be recycled.

### TECHNICAL DATA

**APPEARANCE:** milky, white liquid

**ODOR:** neutral

**pH:** 7.5

**AMMONIA CONTENT:** none

**SOLIDS CONTENT POLYMER:** 22%

**TYPE:** non-zinc interlocked styrene acrylic copolymer

**FLASH POINT:** > 200°F

**SHELF STABILITY:** must protect from freezing

**STATIC COEFFICIENT OF FRICTION:** greater than 0.50 as tested by ASTM D-2047-11

**REMOVAL:** use Ecolution® Floor Stripper

**COVERAGE:** 1,500 - 2,000 square feet per gallon



This product meets the Green Seal™ standard GS-40 based on effective performance, concentrated volume, minimized/ recycled packaging and protective limits on: VOCs and human and environmental toxicity. GreenSeal.org.

## OTHER STATE FLOOR CARE PRODUCTS



**Ecolution® Neutral Floor Cleaner**  
Green-Certified Floor Cleaner



**Ecolution® Floor Stripper**  
Green-Certified Floor Finish Remover



**Floor Wizard™ EZ Guard**  
High-Speed Burnish Restorer and Maintainer



**Restorer**  
Versatile Floor Finish Restorer and Maintainer

### PACKAGING

115796	20 GL Drum
115795	5 GL Pail
119630	1 GL Bottle/CS4



**State Industrial Products**  
5915 Landerbrook Drive  
Mayfield Heights, OH 44124  
To Order Call: 1-866-747-2229  
www.stateindustrial.com

**Canada**  
6935 Davand Drive  
Mississauga, Ontario L5T 1L5  
To Order Call: 1-800-668-6513

**Puerto Rico**  
Royal Industrial Park, Bldg "M"  
Local #5, Carr 869, km 1.5 Palmas  
Cataño, P.R. 00962  
To Order Call: 787-275-3185

